

# L-867 Light Base Non-Load Bearing

Certified to FAA AC 150/5345-42 (Current Edition)  
Size: B=12", D=16", E=24"

*Durable, precision light bases that stand up to harsh conditions.*



## Benefits

- Base galvanized to ASTM A386
- Sturdy installation ensured with (6) 3/8"-16 equally spaced, tapped holes located over conduit openings
- Conduit openings (minimum 2) are located 180° apart and 2.5" up from bottom (various sizes and locations are available)
- Protective plug installed in threaded hubs
- Flex Connex Grommets are shipped separately
- Ground straps available: internal, external or both
- Standard stocked heights:  
AC21242Q200301    AC63242Q200301  
AC21242H200301    AC63242H200301  
Other heights available
- Please contact Airport Lighting Company for non-standard configurations.



AC21242H200301

TYPE	ID	TBC	TID	TOD & BOD
<b>AC21</b> __ 12" L867B	12.375"	10.25"	8"	13.5"
	[314.3]	[260.4]	[203.2]	[342.9]
<b>AC63</b> __ 16" L867D	16.25"	14.25"	12.375"	17.375"
	[412.8]	[362]	[314.3]	[441.3]
<b>AC67</b> __ 24" L867E Modified	22.5"	21.5"	20"	24"
	[571.5]	[546.1]	[508]	[609.6]

[ ] = dimensions in metrics; mm

