


# L802A(L) Hali-Brite® LED Rotating Airport Beacon



## Optional Beacon Tipdown Pole



## Optional Bird Spikes

## Compliances

FAA: L-802A(L) A/C150/5345-12 High Intensity Airport Beacon.

ICAO: Annex 14, Volume 1

## Application

Designed primarily for night operation as identification and location markers for airports

## Key Features

- 75% Power reduction over traditional metal halide lamps
- Instant on- no more waiting for bulbs to get to full bright!
- One white LED lamp, One aviation green LED lamp
- 50,000 hour typical lamp life (12 years)
- Patented belt-drive system eliminates the lubrication required by conventional gear-drive beacons (U.S. Pat. 5,339,224)
- 50,000 hour typical lamp life (12 years)
- Lamps preset 5° above horizontal, adjustable
- Optional stainless steel cabinet & bearings for highly corrosive environments
- Class I (No Heater) normal operating temperature range: 0°F to +131°F (-18°C to +55°C)
- Class 2 (With Heater) normal operating temperature range: -67°F to +131°F (-55°C to +55°C)
- Heater thermostatically controlled to engage at 0°F
- Optional tell-tale relay (monitors lamps and triggers dry contact on outage)
- Power Consumption L-802A(L):  
Class I: 195W, Class II: 595W
- Manufactured in the USA
- AIP Buy American qualified



# Specifications

## Ordering Information

Part #	Description
L802AL116	120 VAC, 60 Hz, Class I
L802AL125	*220-240 VAC, 50 Hz, Class I
L802AL126	*220-240 VAC, 60 Hz, Class I
L802AL216	120 VAC, 60 Hz, Class II
L802AL225	*220-240 VAC, 50 Hz, Class II
L802AL226	*220-240 VAC, 60 Hz, Class II

\*220-240v Models are for overseas applications,  
(220-240 volts LINE TO NEUTRAL)

## Options


Part #	Description
L801/802 T/T LED 120	Tell-Tale Relay 120V
L801/802 T/T LED 240	Tell-Tale Relay 240V 60Hz
L801/802 Bird Spikes	Large polycarbonate resin spikes running along each beacon head to deter birds. UV Stabilized, Clear.
L802 HBM SS	For corrosive environment installations/installations within 100mi of seawater: stainless steel cabinet, bearings, legs and hardware throughout.
4200-0000A	Tower Mounting Kit: Creates a platform from 36" Beacon to all current model beacons
4200-0001A	Tower Mounting Kit, Stainless Steel

## Shipping Information


**Unpackaged Weight:** 77 pounds

**Shipping Weight:** 120 pounds

**Shipping Volume:** 48"x40"x26"



MOUNTING BOLT PATTERN



## Replacement Parts

Part #	Description
0100-3944	Surge Protector
0200-0033	200 W Power Supply
0200-0034	70 W Power Supply
0600-0003	Drive Belt
4100-0000-1A	Motor 120VAC
4100-0006-2	Motor 230VAC
5000-0003	Pulley, Main Shaft
5000-0004	Pulley, Motor
9100-0015	1/2 in Conduit Cover & Gasket
9200-0052	Head Assy, White
9200-0053	Head Assy, GRN (prior 10/2023)
9200-0054	Head Assy, GRN (after 10/2023)